



The **Acclaim** is a recessed luminaire designed for use in solid or plank ceiling types.

Widely used in offshore accommodation modules this proven luminaire is now available in LED bringing all the benefits of long life LED technology with replaceable LED strips and driver.

Mounting Options

- Recessed
- Suspended (drop rods)

International Approvals



Standard Specification

Acclaim LED Recessed Linear

Enclosure	White polyester painted zintec body and frame. Frame colour RAL 9010. Prismatic diffuser.
Geartray	Aluminium
Entry	4 x 21mm clearance holes (supplied plug)
Termination	Quick release mains terminals - 3 core 4mm ² max conductor with looping and through wiring facility (4 core on emergency)
Installation	Fixed side brackets with swing out arms, and provision for drop rod mounting
Control Gear	Electronic Driver
Colour Temperature (CCT)	4000K (Neutral White)
Maintenance	Via front cover, secured by pan head screws
Battery	Internal Ni-Cd (6V) (Emergency version only)
Emergency Duration	3 Hours (02L version = 30% output, 04L version = 15% output)
Ingress Protection	IP54 to EN60529
Surge Protection	4kV
Electrical Supply	220-240V 50/60Hz

Features

- ◆ **Fully maintainable** with replaceable LED strips and driver
- ◆ **Quick release** mains terminal
- ◆ **Resistant** to voltage fluctuations
- ◆ Highly **Energy Efficient**
- ◆ **B15 SOLAS fire rating**
- appropriate insulation is required over the luminaire
- ◆ **Retrofit geartray available**
- ◆ **Battery Monitoring** and automatic self test
- ◆ **80,000 maintenance free hours @ 25°C (L70)**

Chalmit®

LED SOLUTIONS

For Harsh & Hazardous Locations



Product design and specifications are subject to change without notice. Please check the Chalmat website for latest specifications.
www.chalmat.com




MADE IN
BRITAIN

Std. Cat No.	Delivered Output	Power Consumption	Ambient °C	Weight
ACLI/02L/LE	1632 lm	20W	-20 to +45	6.0kg
ACLI/04L/LE	4035 lm	42W	-20 to +45	11.0kg
ACLI/02L/LE/EM	1632 lm	24W	-20 to +45	8.5kg
ACLI/04L/LE/EM	4035lm	47W	-20 to +45	13.5kg

*Note: Installed Industrial Acclaim fluorescents can be upgraded to LED by ordering a Retrofit Geartray ACRI. Substitute ACRI for ACLI in the above partcodes.

Options - Suffix to Catalogue No.

/PC	Solid plank ceiling (Painted frame colour RAL 9016G)	/DM	Digital Dimming (DALI)
/SC	Screwed connection terminal block (up to 6mm ² conductors)	/SSCS	Brushed stainless steel cover (M300 ceiling only)
/EL	Extra live termination facility (compatible with 4 core switched emergency circuits)	/SSC	Brushed stainless steel cover (Solid plank ceiling only)
/25	25mm cable entries	/MF	Mains fuse
/120	Specific voltage (110-130V)	/3K	3000K (Warm White) LED Strips




Model	A	B	Skirt Length	Skirt Width	Cut Out Size
02L	750	720	820	309	800(L) x M300 Tile Width
04L	1365	1335	1435	309	1415(L) x M300 Tile Width



Adjust to ensure ceiling integrity



Single screw height adjustment



Chalmat®

**LED
SOLUTIONS**
For Harsh & Hazardous Locations



Harsh & Hazardous

Chalmat PO BOX 5575 Glasgow G52 9AP
Tel: +44(0) 141 882 5555 Fax: +44(0) 141 883 3704 Email: info@chalmat.com
www.chalmat.com