

ORION



Mounting Options

- Pendant
- Medium Bay
- Low Bay

ce







The **Orion** LED Highbay is a versatile and cost effective luminaire designed to illuminate interior industrial spaces. It's simple design provides high quality economical lighting, available in either an 18,000 lumen or 27,000 lumen package.

The Orion has five different reflector options including clear acrylic, translucent white, opalescent acrylic and suspended bead. There are three lens options, several mounting accessories including cord and plug options and optional bottom wire guards.

Standard Specification

Orion LED Highbay		
Enclosure	Grey painted cast aluminium housing with clear acrylic reflector optic	
Entry	Rigid conduit through top of wire box	
Termination	Within wire box using lever nuts	
Installation	Pendant mounted via rigid conduit	
Control Gear	Electronic Driver	
Colour Temperature (CCT)	5000K (Cool White)	
Maintenance	4 screws on optic chamber cover	
Ingress Protection	IP66 (optic chamber), IP67 (driver)	
Surge Protection	4kV	
Electrical Supply	120-277V AC 50/60Hz	

Features

- Instant on crisp white light output
- Highly Energy Efficient
- 120,000 maintenance free hours at 25°C (L70)
- Lower power consumption than HID lamps
- Low temperature applications to -40°C




www.chalmit.com


Std. Cat No.	Delivered Output	Power Consumption	Ambient °C	Weight
ORII/18L/LE	18335 lm	167W	-40 to +50	6.8kg
ORII/27L/LE	26985 lm	255W	-40 to +40	6.8kg


Options - Suffix to Catalogue No.			
/ww	Translucent white reflector*	/AL	Anodised Aluminium reflector*
/OP	Opalescent acrylic reflector*	/SB	Suspended bead reflector*
/4K	4000K (Neutral White) LEDs	/NR	Without External Reflector

*Reflectors are ordered in place of standard clear acrylic optic

Accessories	Accessories should be ordered separately	
		Order Code
Wire guard		
Conical drop lens		Please contact Chalmit sales for
Dropped lens refractor		information
Frosted acrylic lens		







Product design and specification: are subject to change without notice. Please check the Chalmit website for latest specifications. www.chalmit.com

INDUSTRIAL

SAFE Area









Chalmit PO BOX 5575 Glasgow G52 9AP Tel: +44(0) 141 882 5555 Fax: +44(0) 141 883 3704 Email: info@chalmit.com www.chalmit.com