

BAND-IT®

PRODUCT

ULTRA-LOK® SYSTEM



Designed for quick installation, highest clamping force and gap-free inside diameter. The best choice for demanding applications!

Apply 3-5 times faster than band and buckle hand tools

Unique lock formed under full tension maximizing tightness

201 1/4 hard SS band provides greater material strength allowing tighter clamps and can be double wrapped for additional strength

3/4" band available in plastic totes, buckles sold separately

Buckle hood protects lock from snags

ULTRA-LOK[®] SYSTEM PRODUCT SPECIFICATIONS

PART NO.	MATERIAL	WIDTH (MM)	LENGTH (MM)	THICKNESS (MM)	MAX. DIA. SINGLE WRAP (MM)	MAX. DIA. DOUBLE WRAP (MM)	PACKAGE QUANTITY	WEIGHT (KG)
Ultra-Lok® Band								
UL1018**	201 SS	12.7	457	0.76	76	not suggested	50/Box	1.9
UL1024**	201 SS	12.7	610	0.76	127	64	50/Box	2.4
UL1032**	201 SS	12.7	813	0.76	178	89	50/Box	3.3
UL1046**	201 SS	12.7	1168	0.76	280	140	25/Box	2.7
UL1070**	201 SS	12.7	1778	0.76	457	229	25/Box	3.9
UL1096**	201 SS	12.7	2438	0.76	635	318	25/Box	5.1
UL1116**	201 SS	12.7	2946	0.76	787	394	25/Box	6.0
UL2024	201 SS	19.1	610	0.76	127	not suggested	25/Tote	1.9
UL2032	201 SS	19.1	813	0.76	178	89	19/Tote	2.0
UL2036	201 SS	19.1	914	0.76	252	102	33/Tote	3.7
UL2044	201 SS	19.1	1118	0.76	267	140	27/Tote	3.7
UL2048	201 SS	19.1	1219	0.76	305	153	25/Tote	3.7
UL2052	201 SS	19.1	1321	0.76	330	165	23/Tote	3.7
UL2060	201 SS	19.1	1524	0.76	381	191	20/Tote	3.7
UL2068	201 SS	19.1	1727	0.76	445	216	17/Tote	3.7
UL2076	201 SS	19.1	1930	0.76	508	254	15/Tote	3.7
UL2084	201 SS	19.1	2134	0.76	559	280	14/Tote	3.7
UL2092	201 SS	19.1	2337	0.76	622	305	13/Tote	3.7
UL2120	201 SS	19.1	3048	0.76	826	407	10/Tote	3.7
UL2150	201 SS	19.1	3810	0.76	1029	508	8/Tote	3.7
UL2175	201 SS	19.1	4445	0.76	1232	610	7/Tote	3.7
Ultra-Lok® Buckles								
UB2549	201 SS	12.7						3.7
UB2569	201 SS	19.1						3 5/7

** 1/2" Bands will require M09387 for UL4000 and UL9010 Tool.

3/4" width band lengths 36" or longer in 100' Totes; 34" or less in 50' Totes.

Alloy 625 Ultra-Lok[®] Band

PART NUMBER	MATERIAL	WIDTH (MM)	LENGTH (MM)	MAXIMUM CLAMP DIAMETER	
				SINGLE WRAP (MM)	DOUBLE WRAP (MM)
	Alloy 625	19.1	508	102	not suggested
	Alloy 625	19.1	610	127	not suggested
	Alloy 625	19.1	711	152	not suggested
	Alloy 625	19.1	813	178	89
	Alloy 625	19.1	914	252	102
	Alloy 625	19.1	1016	254	127
	Alloy 625	19.1	1118	267	140
	Alloy 625	19.1	1219	305	153
Call for Part Number & Minimum order Quantity	Alloy 625	19.1	1321	330	165
	Alloy 625	19.1	1524	381	191
	Alloy 625	19.1	1727	445	216
	Alloy 625	19.1	1930	508	254
	Alloy 625	19.1	2134	559	280
	Alloy 625	19.1	2337	622	305
	Alloy 625	19.1	3048	826	407
	Alloy 625	19.1	3810	1029	508
	Alloy 625	19.1	4445	1232	610