

BAND-IT®

PRODUCT

VALU-STRAP™ BAND, VALU- STRAP™ PLUS BAND, AND VALUBAND



BAND-IT® VALU-STRAP™ Band is the light duty stainless steel banding used in applications ranging from strapping to bundling. May be 200 or 300 series Stainless Steel. Typically non-magnetic, this economy steel is suitable for light duty applications when the benefits of stainless steel are required. Also known as Value Series Stainless Steel.

VALU-STRAP™ BAND, VALU-STRAP™ PLUS BAND, AND VALUBAND PRODUCT SPECIFICATIONS

PART NO.	MATERIAL	WIDTH (MM)	THICKNESS (MM)	AVERAGE BREAKING STRENGTH (LBS)	PACKAGE QUANTITY	WEIGHT (KG)
VALU-STRAP™						
C13399	200/300 SS	9.6	0.38	450	30.5m/Roll	1
C13499	200/300 SS	12.7	0.38	600	30.5m/Roll	1.3
C13599	200/300 SS	15.8	0.38	750	30.5m/Roll	1.7
C13699	200/300 SS	19.1	0.38	900	30.5m/Roll	2
C12799	200/300 SS	9.6	0.38	450	61m/Roll	2
C12899	200/300 SS	12.7	0.38	600	61m/Roll	2.6

These products are available in 300' rolls & Full Mill Coil.

PART NO.	MATERIAL	WIDTH (MM)	THICKNESS (MM)	AVERAGE BREAKING STRENGTH (LBS)	PACKAGE QUANTITY	WEIGHT (KG)
VALU-STRAP™ Plus						
C18189	200/300 SS	12.7	0.51	850	30.5m/Roll	1.7
C17199	200/300 SS	15.8	0.51	1000	30.5m/Roll	2.6
C16189	200/300 SS	19.1	0.51	1275	30.5m/Roll	2.5

PART NO.	MATERIAL	WIDTH (MM)	THICKNESS (MM)	AVERAGE BREAKING STRENGTH (LBS)	PACKAGE QUANTITY	WEIGHT (KG)
Valuband						
C14499	200/300 SS	12.7	0.64	1000	30.5m/Roll	2
C14599	200/300 SS	15.8	0.64	1250	30.5m/Roll	2.6
C14699	200/300 SS	19.1	0.64	1590	30.5m/Roll	3

These products are available in 300' rolls & Full Mill Coil.

**The JO2069 Pok-It II Tool with Cutter can be used with 3/8" maximum width product.*